

ADP-15WFPA -FF**Flicker Free Constant Current Source for LED drive**Features

- AC 100-242V wide input voltage range
- Flicker free (10% max) constant current output
18~31V constant current operational range
- PFC correction, PF>0.9
- Low input current THD (Meet IEC61000-3-2 Class C)
- Protections for Short circuit, Over load and Over temp.
- Compact size
- Long life time over 40.000 Hr
- RoHS compatible
- KC, KS-Korea, PSE

Applications

- LED Lighting
- Advertising Light panel
- Down Light

Electrical characteristics

Parameter	Symbol	Conditions	Specification			Unit
			Min	Typ	Max	
Input supply voltage	V_{IN}		90	100	242	V_{AC}
Input current	I_{IN}	$V_{IN}=100V, 12W$	0.12	0.14	0.16	A
Available power input range	P_{IN}	$V_{IN}=100\sim 242V$			12	W
Power factor	$\text{Cos}\theta$	$V_{IN}=100V, 12W$		0.95		
Output current	I_O	$V_{IN}=100\sim 242V$		350		mA
Available output voltage	V_O	$V_{IN}=100\sim 242V$	18		31	V
No load output voltage	V_{O-open}	$V_{IN}=100\sim 242V$			35	V
Efficiency		$V_{IN}=100V, 12W$		82		%

Absolute maximum ratings

Lower Input supply voltage (V_{IN})	-----	90V
Higher Input supply voltage (V_{IN})	-----	265V
Maximum output voltage with load	-----	31V
Minimum output voltage with load	-----	18V
Output current (I_o)	-----	400mA
Input power	-----	12W
Ambient operating temperature	-----	-10 °C to 50 °C
Storage temperature range	-----	-20 °C to 80 °C
Operating & storage humidity	-----	10 % to 85 %

Input & Output Wire or terminals

- AC Input : White & Black, 0.75mm² HVSF, JET/PSE/KS, 180mm Length
- DC Output : DC+ : Red, AWG-22, 230mm Length
DC- : Black, AWG-22, 230mm Length

Mechanical dimensions

Tolerance : ± 0.5
Unit : mm

