

ADP-20WFPA**Constant Current Source for LED drive**Features

- AC 100-242V wide input voltage range
- Constant current output
- 30~44V constant current operational range
- PFC correction, PF>0.9
- Low input current THD (Meet IEC61000-3-2 Class C)
- Protections for Short circuit, Over load and Over temp.
- Encapsulated, Compact size, IP65 available
- Long life time over 40.000 Hr
- High efficiency
- RoHS compatible
- KC, KS-Korea, PSE

Applications

- LED Lighting
- Advertising Light panel
- Down Light

Electrical characteristics

Parameter	Symbol	Conditions	Specification			Unit
			Min	Typ	Max	
Input supply voltage	V_{IN}		90	220	242	V_{AC}
Input current	I_{IN}	$V_{IN}=220V, 18W$	0.08	0.09	0.10	A
Available power input range	P_{IN}	$V_{IN}=100\sim 242V$			18	W
Power factor	$\text{Cos}\theta$	$V_{IN}=220V, 18W$		0.94		
Available output current	I_O	$V_{IN}=100\sim 242V$		400		mA
Available output voltage	V_O	$V_{IN}=100\sim 242V$	30		44	V
No load output voltage	V_{O-open}	$V_{IN}=100\sim 242V$			50	V
Efficiency		$V_{IN}=220V, 18W$		85		%

Absolute maximum ratings

Lower Input supply voltage (V_{IN})	-----	90V
Higher Input supply voltage (V_{IN})	-----	265V
Maximum output voltage with load	-----	44V
Minimum output voltage with load	-----	30V
Output current (I_o)	-----	400mA
Input power	-----	18W
Ambient operating temperature	-----	-10 °C to 50 °C
Storage temperature range	-----	-20 °C to 80 °C
Operating & storage humidity	-----	10 % to 85 %

Input & Output Wire or terminals

AC Input	:	White & Black, 0.75mm ² HVSF, JET/PSE/KS, 180mm Length
DC Output	:	DC+ : Red, AWG-22, 230mm Length
		DC- : Black, AWG-22, 230mm Length

Mechanical dimensions

Tolerance : ± 0.5
Unit : mm

